


	<p><b><u>SPD</u></b> <i>Square Plaque Diffuser</i></p> <p><b><u>ASPD</u></b> <i>Alum. Square Plaque Diffuser</i></p>	<ul style="list-style-type: none"> <li>• Easily installed and removable face panel.</li> <li>• Tight 360° horizontal air pattern even at low air volume.</li> <li>• Complete range of accessories</li> <li>• MRI application (ASPD only)</li> <li>• 24"x24", 20"x20", 12"x12"</li> </ul>
	<p><b><u>SCD</u></b> <i>Square Cone Diffuser</i></p> <p><b><u>ASCD</u></b> <i>Alum. Square Cone Diffuser</i></p>	<ul style="list-style-type: none"> <li>• All sizes available with 3 concentric cones</li> <li>• 4 cone available for 24"x24" size for aesthetic considerations</li> <li>• Complete range of accessories</li> <li>• MRI application (ASCD only)</li> <li>• 24"x24", 20"x20", 12"x12"</li> </ul>
	<p><b><u>PDF</u></b> <i>Perforated Face Supply Diffuser</i></p> <p><b><u>APDF</u></b> <i>Alum. Perforated Face Diffuser</i></p> <p><b><u>PDFE/APDFE</u></b> <i>Extended Face</i></p>	<ul style="list-style-type: none"> <li>• Hinged, removable faceplate with quick release spring latches</li> <li>• Field adjustable, louvered face air pattern controllers located on face</li> <li>• Complete range of accessories</li> <li>• MRI application (PDS model)</li> <li>• 12"x12", 24"x12", 16"x16", 20"x20", 24"x24"</li> </ul>
	<p><b><u>500 Series</u></b> <i>Steel Louvered Supply/Return</i></p> <p><b><u>600 Series</u></b> <i>Alum. Louvered Supply/Return</i></p> <p><b><u>700 Series</u></b> <i>SS Louvered Supply/Return</i></p>	<ul style="list-style-type: none"> <li>• Single Deflection: 510, 610, 710</li> <li>• Double Deflection: 520, 620, 720</li> <li>• Return: 530, 630, 730</li> <li>• 3 Border Styles, 2 blade spacing option</li> <li>• Optional opposed blade damper</li> <li>• MRI application (630/630FF only)</li> <li>• Matching Filter Grilles (530FF/630FF)</li> </ul>
	<p><b><u>PDDR</u></b> <i>Perforated Ceiling Return Diff.</i></p> <p><b><u>APDDR</u></b> <i>Alum. Perforated Ceiling Return</i></p> <p><b><u>PDDRE/APDDRE</u></b> <i>Extended Face</i></p>	<ul style="list-style-type: none"> <li>• Hinged, removable faceplate with quick release spring latches</li> <li>• Duct and plenum return options</li> <li>• 5 frame styles</li> <li>• Complete range of accessories</li> <li>• MRI application (PDR model only)</li> <li>• 12"x12", 24"x12", 16"x16", 20"x20", 24"x24", 48"x24"</li> </ul>
	<p><b><u>TBD Series</u></b> <i>T-Bar Diffusers</i></p>	<ul style="list-style-type: none"> <li>• <b>TBD2:</b> Extruded curved pattern controller</li> <li>• <b>TBD3:</b> Extruded "ice tong" blade</li> <li>• <b>TBD4:</b> Blade type pattern controller</li> <li>• <b>TBD6:</b> Fixed horizontal air pattern with high induction ratio</li> <li>• <b>TBD7:</b> Fixed horizontal air pattern</li> </ul>
	<p><b><u>SDV5</u></b> <i>Single Duct Terminal Unit, Digital Control provided by others</i></p> <p><i>Please reference website or catalog (pg F47) for further performance and information</i></p>	<p><u>Recommended Air Volume Ranges</u></p> <ul style="list-style-type: none"> <li>• 4" – 45-400 CFM</li> <li>• 6" – 65-550 CFM</li> <li>• 8" – 125-1100 CFM</li> <li>• 10" – 210-1800 CFM</li> <li>• 12" – 300-2600 CFM</li> <li>• 14" – 430-3700 CFM</li> </ul>
	<p><b><u>FDV5</u></b> <i>Parallel Fan Powered, Digital Control provided by others</i></p> <p><i>Please reference website or catalog fan curves (pg F405-F408) for further size and performance information</i></p>	<p><u>Recommended Air Volume Ranges</u></p> <ul style="list-style-type: none"> <li>• 6" – 66-450 CFM</li> <li>• 8" – 132-800 CFM</li> <li>• 10" – 221-1350 CFM</li> <li>• 12" – 310-2100 CFM</li> <li>• 14" – 439-3000 CFM</li> <li>• 16" – 568-4000 CFM</li> </ul>